



MOBILE ENERGY SOLUTIONS FOR ENHANCED RELIABILITY, RESILIENCY, AND ELECTRIFICATION

PROMIS[®] Portable, Robust, Microgrid Integrated Storage System

PROMIS is a portable energy storage system primarily designed for emergency energy supply to single- and three-phase customers.

PROMIS is designed for frequent relocation and fast interconnection at a new site using a standard generator terminal box with Cam-lok[™] plugs. PROMIS offers a clean replacement for emergency (portable) diesel generators and can operate in grid-connected mode for grid support functions.

PROMIS' platform is equipped with integrated microgrid technology and an on-board controller that provides comprehensive sets of autonomous controls, optimization schemes, and supervisory capability for ease of remote operator access and integration back to the Dispatch Center for overall grid coordination.



PICTURED: PROMIS trailer



PICTURED: PROMIS non-walkable battery room

Features and Benefits

Improved Safety and Environmentally Friendly

- Reliable, fire-resistant, and safe battery-cell technology.
- Non-walkable and modular design compliant with UL 9540.
- Explosion- and fire-resistant battery cabinets (NEMA rated).
- Additional fire-suppression systems designed to meet the NFPA 855 fire-protection standard.
- Sound-attenuated containerized enclosure.
- Vibration, tension, and impact detection sensors.

Mature Technology

- UL-certified Battery Management System (BMS).
- Lithium iron-phosphate (LiFePO₄) battery cells.
- High full-cycle charge rate (>6,000 cycles).

Portability

- Containerized solution with no transportation permit required per most Departments of Transportation (DOT).
- Installed on a flat-bed or step-deck trailer for easy transport.
- Anti-vibration and shock-absorbent design.

Plug-and-Play Interconnection

- Compliant with IEEE 1547-2018 interconnection requirements using standard switches.
- Includes a visible load-break disconnect switch, fault-interruption circuit breaker, and synchronizing devices.
- Contains an isolation transformer for interconnection with fuse and circuit breaker overcurrent protection.

CONTACT US:

648-278-5883

[quanta-technology.com](https://www.quanta-technology.com)

RE-VAN.Sales@Quanta-Technology.com

[LinkedIn.com/company/quanta-technology](https://www.linkedin.com/company/quanta-technology)



Mobile. Clean. Quiet.

An Ideal Replacement for Emergency Diesel Generators

Outage Management and Maintenance Support

PROMIS replaces traditional forms of backup generation units (e.g., diesel generators) for supplying customers during service interruptions due to outage or maintenance.

Peak Load and Demand Change Management

PROMIS provides peak-shaving capabilities during periods of high demand or high electricity prices to relieve loading on a utility's assets and to achieve global cost reduction.

Voltage Control

PROMIS mitigates and improves commonly experienced voltage issues to enhance customers' power quality on the distribution system through corrective actions.

Power Conversion System (PCS) and Intertie	100 kVA Single-phase	250 kVA Three-phase	500 kVA Three-phase
Rated power output at 86 °F (30 °C) and nominal voltage	100 kW, up to 1 MWh for 20' container	250 kW, up to 1 MWh for 20' container	500 kW, up to 1 MWh for 20' container
Interconnection voltage	120 / 240 V	<ul style="list-style-type: none"> 120 / 240 V 480 / 208 V U.S. standard listing; 600 V Canadian standard listing 	
AC output	Single / split phase (isolated)	<ul style="list-style-type: none"> Single/split-phase (isolated) Three-phase, four-wire ungrounded, isolated (grid connected) Grounded (standalone) 	
AC current (nominal)	312 A	<ul style="list-style-type: none"> 300 A (480 V) 240 A (600 V) 	<ul style="list-style-type: none"> 600 A (480 V) 480 A (600 V)
Grid frequency	57 - 63 Hz	57 - 63 Hz	57 - 63 Hz
Current harmonic distortion	<3%	<3%	<3%
Protection	<ul style="list-style-type: none"> Circuit breaker with manual (visible) disconnect switch for grid side Type SEL-751 protection relay for interconnection 		
Communications	<ul style="list-style-type: none"> ModBus/DNP3 (TCP): third-party SCADA interface (secure) LTE cellular (asset monitoring) 		
Standards compliance	IEEE 1547, UL 1741, UL 1973, UL 9540 and UL 9540A (cell/module), NFPA 855		

Container	
Onboard standby auxiliary power	120 / 240 V UPS (6.8 kVA, 10 kWh)
Auxiliary power consumption	5 kW maximum
Container dimensions L x W x H in ft	Container only 20' x 8' x 8.6'
Weight lbs (kg)	<45,000 (20,412)
Fully integrated HVAC	9,200 BTU/hr unit with thermostat control (quantity two primary and backup)
Fire-suppression system	Fire suppression, smoke / gas detector
NEMA rating / IP class	NEMA 3R / IP54
Elevation (operating) in ft (m)	<8,202 (<2,500)
Ambient operating temperature	-40 °F to +104 °F (-40 °C to +40 °C)

Battery System	
Cell technology	Lithium iron-phosphate (LiFePO4)
Voltage range (dc)	670 - 1,200 Vdc
Recommended charge / discharge current	0.5 C/1.0 C

Quanta Technology, LLC.

4020 Westchase Blvd.
Raleigh, North Carolina 27607

©02/2023, Quanta Technology, LLC.

Document number: QTECH-FL-06-V3-02-23

Quanta Technology, LLC has used reasonable efforts to ensure the accuracy and completeness of the technical data presented in this document. Quanta Technology, LLC makes no warranty or representation for its contents, including technical and/or business considerations, risk, impacts, intended or unintended consequences, or outcomes that may determine the value or use of this document. Specific technical data can be provided upon request. Quanta Technology, LLC reserves the right to modify the technology and data contained herein at any time.

CONTACT US:

648-278-5883

quanta-technology.com

info@quanta-technology.com

[LinkedIn.com/company/quanta-technology](https://www.linkedin.com/company/quanta-technology)